




LabSat 3



LabSat 3 Wideband



LabSat Real-Time

Constellations	GPS L1 GLONASS G1 BeiDou B1	GPS L1, L2, L5; Galileo E1, E5a/b, E6; GLONASS L1, L2, L3; BeiDou B1, B2, B3; QZSS L1, L2, L5; IRNSS L5; In-band SBAS Further signals in the upper and lower L band can be configured with the internal webserver. Bespoke requirements like Iridium & Sirius XM radio frequencies are available on request	GPS L1 GLONASS G1 BeiDou B1
RF Channels	1,2 or 3 (model dependant)	3	2
RF Centre Frequency	GPS L1 - 1575.420 MHz GLONASS - G1 1602.00 MHz BeiDou B1 - 1561.098 MHz	User Selectable	GPS L1 - 1575.420 MHz GLONASS G1 - 1602.00 MHz BeiDou B1 - 1561.098 MHz
Bandwidth	9.66 MHz	10 MHz, 30 MHz, 56 MHz	16 MHz
Quantisation	1 bit, 2 bit	1 bit, 2 bit, 3 bit	1 bit, 2 bit
Sample Frequency	16.368 MHz	10.23 MHz, 30.69 MHz, 58 MHz	16.368 MHz
Removable Battery	Yes	Yes	No
Output Signal Level	Adjustable -73dBm to -103dBm	Adjustable -73dBm to -162dBm	Adjustable -83dBm to -107dBm
Reference Oscillator	Accuracy (ppm) TCXO ± 2.5 ; OCXO ± 0.3 Aging (ppm/year) TCXO ± 1 ; OCXO ± 0.3 Stability (ppm/ °C) TCXO ± 0.05 ; OCXO ± 0.05	Temperature Stability (ppm) TCXO ± 0.05 ; OCXO ± 0.05 Frequency Stability (ppm over first year) TCXO ± 1 ; OCXO ± 0.3	Temperature Stability TCXO ± 2.5 ppm Long Term Stability TCXO ± 1.0 ppm
Operating Voltage	8 - 30 V DC	8 - 30 V DC	8 - 30 V DC
Dimensions	167 x 128 x 43 (mm)	167 x 128 x 46 (mm)	170 x 128 x 46 (mm)
Weight	960 g with battery (910 g without)	1.2 kg	750 g